

1. Unique identification code of the product-type:

**Sopro MEG 667**

2. Intended use::

**Improved, fast setting cementitious adhesive for tiling internal and external floors and walls**

3. Manufacturer:

**Sopro Bauchemie GmbH, Biebricher Straße 74, 65203 Wiesbaden (Germany), www.sopro.com**

4. Systems of AVCP:

**System 3 for initial type testing  
System 3 for reaction to fire**

5. Harmonized standards:

**EN 12004:2007 + A1:2012**

Notified bodies:

The notified laboratory Kiwa Polymer Institut, No. 1119, carried out the assessment of the performance for type testing on the basis of testing on samples taken by the manufacturer according to system 3 and issued the classification report No. P 9255.

The notified laboratory MPA Dresden GmbH, No. 0767, carried out the assessment of the performance for reaction to fire on the basis of testing on samples taken by the manufacturer according to system 3 and issued the classification reports No. 20151175/01 and No. 20151175/04.

6. Performances declared:

Essential characteristics	Performance
Reaction to fire	Class B-s1, d0 / B <sub>fl</sub> -s1
Bond strength as: - early tensile adhesion strength - initial tensile adhesion strength	≥ 0,5 N/mm <sup>2</sup> ≥ 1,0 N/mm <sup>2</sup>
Durability for: - tensile adhesion strength after heat ageing - tensile adhesion strength after water immersion - tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm <sup>2</sup> ≥ 1,0 N/mm <sup>2</sup> ≥ 1,0 N/mm <sup>2</sup>
Release of dangerous substances	siehe SDS

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by::

Wiesbaden, 24/02/2016

  
  
 ppa. Helmut Schäfer, Head of Product Technology  
 65203 Wiesbaden  
 Produktüberwachung